

**AUTHORIZATION TO FILE DOCUMENTS INCORPORATED
BY REFERENCE BY DESCRIPTION**

Submit this form to request an exemption from the requirements of filing in full textual material adopted by reference into regulations. Questions, contact Office of the Registrar of Regulations.

① Agency: Board of Agriculture and Consumer Services

② VAC Number/Chapter Title: 2VAC5-425, Vapor Pressure Requirements for Gasoline Ethanol Blends

③ Effective Date of Final Regulation (leave blank for proposed stage): April 19, 2016-October 18, 2017 (emergency regs)

④ Name of Document Incorporated by Reference (include edition or effective/revised date):
Standard Specification for Automotive Spark-Ignition Engine Fuel, ASTM D4814-16a

⑤ Summary or description of the document incorporated by reference:
See attached

⑥ Is a copy of the document incorporated by reference in custody of the agency and available to the public for inspection and copying as required by § 2.2-4103? YES NO

⑦ Document may be inspected at the following agency location:
VDACS - Office of Weights and Measures
Oliver Hill Building
102 Governor Street
Richmond, VA 23219

Document may be obtained from the following entity (include website and cost of document):
ASTM International
P.O. Box C700
West Conshohocken, PA 19248
www.astm.org
Cost: \$64.00

⑧ Explain why it is impractical to file a copy of the document incorporated by reference:
1VAC7-10-170 B. Filing the incorporated document in its entirety would be impractical, as the document is copyrighted and the agency is prohibited from reproducing the document in its possession.

⑨ Attach a copy of the document cover, title page, and copyright page.

Requested by: Erin Williams, (804) 786-7157

Print Name/Telephone Number of Agency Regulatory Coordinator

Erin Williams

Signature of Agency Regulatory Coordinator

April 19, 2016

Date

Approved:

James Perie
Assistant Registrar of Regulations

April 20, 2016

Date

Authorization to File Documents Incorporated by Reference by Description - Summary of Document

Agency: Board of Agriculture and Consumer Services

Regulation: 2 VAC 5-425 *et seq.*, *Vapor Pressure Requirements for Gasoline Ethanol Blends*

Document Incorporated by Reference: Standard Specification for Automotive Spark-Ignition Engine Fuel, ASTM D4814-16a

Publication date: February 2016

Standard Specification for Automotive Spark-Ignition Engine Fuel, ASTM D4814-16a, establishes requirements of liquid automotive fuels for ground vehicles equipped with spark-ignition engines. This standard was adopted by ASTM International, one of the world's largest international standards developing organizations.



Standard Specification for Automotive Spark-Ignition Engine Fuel¹

This standard is issued under the fixed designation D4814; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

This standard has been approved for use by agencies of the U.S. Department of Defense.

1. Scope*

1.1 This specification covers the establishment of requirements of liquid automotive fuels for ground vehicles equipped with spark-ignition engines.

1.2 This specification describes various characteristics of automotive fuels for use over a wide range of operating conditions. It provides for a variation of the volatility and water tolerance of automotive fuel in accordance with seasonal climatic changes at the locality where the fuel is used. For the period May 1 through Sept. 15, the maximum vapor pressure limits issued by the United States (U.S.) Environmental Protection Agency (EPA) are specified for each geographical area except Alaska and Hawaii. Variation of the antiknock index with seasonal climatic changes and altitude is discussed in Appendix X1. This specification neither necessarily includes all types of fuels that are satisfactory for automotive vehicles, nor necessarily excludes fuels that can perform unsatisfactorily under certain operating conditions or in certain equipment. The significance of each of the properties of this specification is shown in Appendix X1.

1.3 The spark-ignition engine fuels covered in this specification are gasoline and its blends with oxygenates, such as alcohols and ethers. This specification does not apply to fuels that contain an oxygenate as the primary component, such as Fuel Methanol (M85). The concentrations and types of oxygenates are not specifically limited in this specification. However, depending on oxygenate type, as oxygenate content increases above some threshold level, the likelihood for vehicle problems also increases. The composition of both unleaded and leaded fuel is limited by economic, legal, and technical consideration, but their properties, including volatility, are defined by this specification. In addition, the composition of unleaded fuel is subject to the rules, regulations, and Clean Air Act waivers of the U.S. Environmental Protection Agency (EPA). With regard to fuel properties, including volatility, this

specification can be more or less restrictive than the EPA rules, regulations, and waivers. Refer to Appendix X3 for discussions of EPA rules relating to fuel volatility, lead and phosphorous contents, deposit control additive certification, and use of oxygenates in blends with unleaded gasoline. Contact the EPA for the latest versions of the rules and additional requirements.

1.4 This specification does not address the emission characteristics of reformulated spark-ignition engine fuel. Reformulated spark-ignition engine fuel is required in some areas to lower emissions from automotive vehicles, and its characteristics are described in the research report on reformulated spark-ignition engine fuel.² However, in addition to the legal requirements found in this research report, reformulated spark-ignition engine fuel should meet the performance requirements found in this specification.

1.5 This specification represents a description of automotive fuel as of the date of publication. The specification is under continuous review, which can result in revisions based on changes in fuel, automotive requirements, or test methods, or a combination thereof. All users of this specification, therefore, should refer to the latest edition.

NOTE 1—If there is any doubt as to the latest edition of Specification D4814, contact ASTM International Headquarters.

1.6 Tests applicable to gasoline are not necessarily applicable to its blends with oxygenates. Consequently, the type of fuel under consideration must first be identified in order to select applicable tests. Test Method D4815 provides a procedure for determining oxygenate concentration in mass percent. Test Method D4815 also includes procedures for calculating mass oxygen content and oxygenate concentration in volume percent. Appendix X4 provides a procedure for calculating the mass oxygen content of a fuel using measured oxygenate type, oxygenate concentration in volume percent, and measured density or relative density of the fuel.

1.7 The following applies to all specified limits in this standard: For purposes of determining conformance with these specifications, an observed value or a calculated value shall be rounded "to the nearest unit" in the right-most significant digit

¹ This specification is under the jurisdiction of ASTM Committee D02 on Petroleum Products, Liquid Fuels, and Lubricants and is the direct responsibility of Subcommittee D02.A0.01 on Gasoline and Gasoline-Oxygenate Blends.

Current edition approved Feb. 1, 2016. Published February 2016. Originally approved in 1988. Last previous edition approved in 2016 as D4814 – 16. DOI: 10.1520/D4814-16A.

² Supporting data have been filed at ASTM International Headquarters and may be obtained by requesting Research Report RR:D02-1347.

*A Summary of Changes section appears at the end of this standard